

Two Wheel Trucks

Capacity Range

500 – 1,400 lbs.



★HM44-E

★HM44-K



★HM52-B
Shown with 8" Ace-Tuf® Rubber-tired wheels.



★HM53-K



Designed for proper balance and rigidly welded of high alloy steel tubing, *Lite-N-Tuf®* all-welded steel hand trucks embody Hamilton quality at a competitive price. Steel frames of 1 1/8" O.D. high yield tubing, red enamel finish (yellow on HM44-K and HM53-K), and vinyl handle grips are standard features on these models.

HM52-B and HM44-E hand trucks feature solid bar steel curb skids, beveled nose edges, strong "back-up" nose design, and extra large stair skids. Choice of wheels listed below.

HM44-K is the widest model available and is furnished standard with 6" x 2" *Versa-Tech®* wheels.

HM53-K features 8" x 2.50 *Ace-Tuf®* ball bearing wheels, and a 65" tall frame ideal for carrying bread racks or other bulky high loads.

Newly added model HM44-S is all stainless steel, including hardware. Wheels have *Delrin®* bearings.

SPECIFICATIONS (inches)					
Model No.	HM44-E	HM44-K	HM52-B	HM53-K	HS44-S
Height	46	48	46	65	45
Frame Width	15	18 1/4	15	15	15
Overall Width	20%	24	21	21	20%
Nose Depth	8	6 3/4	8	9	8
Capacity Lbs.	500	500	500	500	500
Weight Lbs.	30	35	35	40	30

★ = two-day **PRONTO®** shipment.

HM44/52/53/HS44 Selection Table

SELECTION SUFFIX					
Ace-Tuf®		Pneumatic	Semi-Pneumatic	Versa-Tech®	
8 x 2.50	10 x 2.75	10 x 4.10-4	6 x 2.00	6 x 2	8 x 2
-8AT★	-10AT★	-10PR★	-6SP★	-6TE★	-8TE★

TO ORDER, SPECIFY MODEL NUMBER AND SELECTION SUFFIX

WHEEL CHOICES for more help, see pages 14 & 15



Ace-Tuf®



Semi-Pneumatic



Pneumatic Rubber tires



Versa-Tech®

★HS44-S

