

Platform Trucks Capacity Range 4,000 – 5,000 lbs.



PW907-A
Narrow track to fit scales.



PM5600-A
Heavy duty, all steel.

To order, specify model number and suffixes.

PW907 & PM5600 Selection Table

Platform Size Inches	SELECTION SUFFIX								
	Wheels 16" x 3" and 10" x 3" Platform Height 17 ³ / ₄ "				Wheels 18" x 3" and 12" x 3" Platform Height 18 ³ / ₄ "				
	Metal	Moldon Rubber	Plastex	Weight Lbs.		Metal	Moldon Rubber	Weight Lbs.	
				Model PW907	Model PM5600			Model PW907	Model PM5600
30 x 60	-16M3060	-16R3060	-16P3060	270	320	-18M3060	-18R3060	325	340
36 x 60	-16M3660	-16R3660	-16P3660	285	350	-18M3660	-18R3660	340	370
36 x 72	-16M3672	-16R3672	-16P3672	300	365	-18M3672	-18R3672	355	395
36 x 84	-16M3684	-16R3684	-16P3684	320	390	-18M3684	-18R3684	375	420
36 x 96	-16M3696	-16R3696	-16P3696	X	405	-18M3696	-18R3696	X	435
42 x 72‡	-16M4272	-16R4272	-16P4272	X	385	-18M4272	-18R4272	X	415
42 x 84‡	-16M4284	-16R4284	-16P4284	X	415	-18M4284	-18R4284	X	445
48 x 84‡	-16M4884	-16R4884	-16P4884	X	470	-18M4884	-18R4884	X	480

‡ PM5600 only.

QUALITY FEATURES

- Load wheels 16" x 3" for 4,000 lbs. capacity, or 18" x 3" for 5,000 lbs. capacity, on 1¹/₄" dia. common axle.
- Forged steel swivel casters #S-CH-12 with 10" x 3" wheels for 4,000 lbs. capacity, or #S-CH-12 with 12" x 3" wheels for 5,000 lbs. capacity
- Roller bearings and lube fittings in all wheels.

UNIQUE SPECIFICATIONS

PW907 has 1" select hardwood deck and 2" x 4" hardwood frame with reinforcing center longitudinal. Rounded corners and internal pipe sockets at both ends. Available with Superstructure Styles A, C, F, G, H, I, J, and K.

PM5600 has 12 ga. smooth steel deck welded to 3" steel channel frame and reinforcing center longitudinal. Mitered corners at both ends. Available with Superstructure Styles A, G, H, and J.

QUALITY FEATURES

- Flush 1" hardwood deck set in 3" x 2" x 3/16" steel angle frame with reinforcing center longitudinal.
- Forged steel swivel casters #S-CH-12 with 10" x 3" wheels, and 16" x 3" load wheels on 1¹/₄" dia. common axle. Roller bearings and lube fittings in all wheels.
- Channel-reinforced pipe sockets with set screws.
- Platform height 17³/₄".
- Capacity 4,000 lbs.

Available with Superstructure Styles A, G, H, and J.



PB1018-A
Top-of-the-line
Steel & Wood.

PB1018 Selection Table

Platform Size Inches	SELECTION SUFFIX			Approx. Weight Lbs.
	Metal	Moldon Rubber	Plastex	
30 x 60	-M3060	-R3060	-P3060	290
36 x 60	-M3660	-R3660	-P3660	305
36 x 72	-M3672	-R3672	-P3672	325
36 x 84	-M3684	-R3684	-P3684	350
42 x 72	-M4272	-R4272	-P4272	390
42 x 84	-M4284	-R4284	-P4284	415
42 x 96	-M4296	-R4296	-P4296	445

To order, specify model number and suffixes.

WHEEL CHOICES for more help, see pages 14 & 15



Metal:
cast iron, heavy duty design



Plastex:
phenolic, low cost, high capacity



Moldon Rubber:
1" thick 70D rubber, tensile strength exceeds 1,000 psi

