

**Tilt-Type Platform Trucks**

**Capacity Range**  
**2,200 – 3,500 lbs.**

**QUALITY FEATURES**

- Sanded and varnished deck of 1" select hardwood on 2" x 6" side sills; cross bolsters 1¼" hardwood.
- Countersunk screw nails; lock washers on all bolts.
- Reinforcing steel tie rod across each end.
- Heavy duty cast stake sockets and axle brackets.
- Load wheels 12" x 2½" on 1" diameter axle with 6" x 2" end casters, or 16" x 3" on 1" diameter axle with 8" x 2" end casters.
- Roller bearings and lube fittings in all wheels.
- Platform height 16¼" with 12" and 6" wheels, 18¼" with 16" and 8" wheels.

★ All models shippable PRONTO® with Superstructure Styles L and M.

★ **PW820-M**  
One swivel caster each end, tilt-type.



★ **PW840-M**  
Two swivel casters each end, tilt-type.



★ = two-day PRONTO® shipment.


**PW820/840, PB1120/1140, PM5520/5540 Selection Table**

TO ORDER, SPECIFY MODEL NUMBER AND SUFFIX

Platform Size Inches	SELECTION SUFFIX											
	Wheels 12" x 2½" and 6" x 2"						Wheels 16" x 3" and 8" x 2"					
	Capacity 2,200 lbs. with 2 casters, 2,700 lbs. with 4 casters			Capacity 3,000 lbs. with 2 casters, 3,500 lbs. with 4 casters								
	Metal	Moldon Rubber	Plastex	Approx. Weight Lbs. ‡			Metal	Moldon Rubber	Plastex	Approx. Weight Lbs. ‡		
				PW820	PB1120	PM5520				PW820	PB1120	PM5520
24 x 48†	-12M2448★	-12R2448★	-12P2448★	180	180	215	-16M2448★	-16R2448★	-16P2448★	215	265	245
30 x 48	-12M3048★	-12R3048★	-12P3048★	215	215	250	-16M3048★	-16R3048★	-16P3048★	235	310	270
30 x 60	-12M3060★	-12R3060★	-12P3060★	225	240	270	-16M3060★	-16R3060★	-16P3060★	245	340	290
36 x 60	-12M3660★	-12R3660★	-12P3660★	240	260	290	-16M3660★	-16R3660★	-16P3660★	260	365	310
36 x 72	-12M3672★	-12R3672★	-12P3672★	255	290	315	-16M3672★	-16R3672★	-16P3672★	275	400	335

† N.A. in six-wheel models.

‡ Add Approx. 25 lbs. for Models PW840, PB1140 and PM5540.



**WHEEL CHOICES** for more help, see pages 14 & 15



**Metal:** cast iron, heavy duty design



**Plastex:** phenolic, low cost, high capacity



**Moldon Rubber:** 1" thick 70D rubber, tensile strength exceeds 1,000 psi