

# Track

**Load Rating (ea.): 500 – 18,000 lbs.**

Ready to take loads off the factory floor and kick production into high gear? Hamilton's line of ultra-durable, smooth rolling, v-grooved, flanged and u-groove wheels run on in-plant tracks to create an instant production line. Transport auto parts, packaged goods, frozen foods and practically anything on an inverted angle iron (V-grooved), curved track, tube or a rail-type track.

**Industries & Applications:**

- Manufacturing plants
- Assembly fixtures
- Production lines
- In-floor conveyors
- Autoclaves
- Cranes, pulleys & hoists



**Steel/Iron V-Groove**

**Load Rating (ea.): 325 – 16,500 lbs.**

- Cast iron or forged steel offerings
- Wide range of mounting plates
- Custom sizes available



**Single Flange Track**

**Load Rating (ea.): up to 18,000 lbs.**

- Flange on one side of wheel
- Cast iron or forged steel wheels
- Custom specs & higher capacities available



**Stainless Steel V-Groove**

**Load Rating (ea.): up to 1000 lbs.**

- Type 303 for corrosive environments
- Choose from Delrin or Stainless Steel Precision Ball Bearings
- Custom sizes available



**Double Flange Track**

**Load Rating (ea.): up to 18,000 lbs.**

- Flanges on both sides of wheel
- Wide range of mounting plates
- Wheel Diameters: 3 1/2" - 15"



### Steel & Cast Iron V-Groove

**Load Rating (ea.): 1300 - 7500 lbs.**

- Cast iron & forged steel models
- Keyways and/or setscrews opt



### Stainless Steel V-Groove

**Load Rating (ea.): 500 - 1500 lbs.**

- Corrosive, sanitary, or high heat apps
- Keyways and/or setscrews opt.



### Steel & Cast Iron Single Flange

**Load Rating (ea.): Up to 18,000 lbs.**

- Flange on one side of wheel
- Wide range of mounting plates
- Run on ASCE Rail or other types



### Steel & Cast Iron Double Flange

**Load Rating (ea.): 2500 - 18,000 lbs.**

- Flange on one side of wheel
- Wide range of mounting plates
- Run on ASCE Rail or other types



### Nylast® Single Flange

**Load Rating (ea.): 1000 - 2000 lbs.**

- Heavy duty cast nylon
- Viable alternative to steel
- Resistance to moisture & chemicals



### Nylast® Double Flange

**Load Rating (ea.): 1000 - 2000 lbs.**

- Heavy duty cast nylon
- Wheel Diameters: 3" - 12"
- Resistance to moisture & chemicals



### Phenolic V-Groove

**Load Rating (ea.): Up to 1250 lbs.**

- Lowest cost option
- Quieter than metal
- Custom sizes available



### U-Groove

**Load Rating (ea.): Up to 7,500 lbs.**

- Runs on round tubing or pipe
- Nylast, forged and stainless steel available as standard products
- Other available materials polyurethane, UHMW and aluminum



Scan to learn how Hamilton's casters and wheels keep you on track.

